



# PRECISION REROLLED

## STAINLESS STEEL, NICKEL & COBALT STRIP



### REROLL CAPABILITIES

- Extreme Precision Tolerances
- Fully Certified AMS and ASTM Specs
- DFARS Compliant Material



### REROLL EQUIPMENT

- Sendzimir Cold Reversing Mill
- Strip Cleaning Line
- Bright Annealing Furnace
- Slitting Line



### INDUSTRIES SERVED

- Aerospace
- Medical
- Power Generation
- Automotive
- Photo-Etching
- Springs
- Electronics
- Fasteners
- Washers
- Strapping
- Filters
- Gaskets
- Hose Clamps
- Appliances
- Refrigeration

## PRECISION REROLLED STRIP SOLUTIONS

United Performance Metals now offers precision rerolled strip in stainless steel, nickel alloys, and cobalt to your exacting specifications. By leveraging our people, products, and FIRSTCUT+® Processing Services, our new rerolling mill is the latest example of how we are expanding to meet our customer's needs.



888.282.3292

[sales@upmet.com](mailto:sales@upmet.com)

[www.upmet.com](http://www.upmet.com)

# PRECISION REROLLED STRIP

<b>STAINLESS STEEL</b>	<b>301</b>	<b>302/304</b>	<b>304L</b>	<b>305</b>	<b>316/316L</b>	<b>321</b>	<b>347</b>		
<b>NICKEL ALLOYS</b>	<b>201</b>	<b>600</b>	<b>625</b>	<b>718</b>	<b>X750</b>	<b>A286</b>	<b>ALLOY X</b>	<b>C276</b>	<b>WASPALLOY®</b>
<b>COBALT ALLOYS</b>	<b>L605</b>								

<b>THICKNESS RANGE</b>	.0008" - .015"
<b>WIDTH RANGE</b>	.200" — 12.00" #3 Slit Edge 12.50" Mill Edge
<b>CERTIFICATIONS</b>	Full chemical and mechanical certification provided to ASTM and/or AMS specifications DFARS/Domestic available as needed
<b>BRIGHT ANNEALING</b>	Controlled hydrogen atmosphere annealing for a brighter finish
<b>ALL TEMPER</b>	1/8, 1/4, 1/2, 3/4, Full Hard, Spring Temper available in 301, 302 and 304 Can also be processed to customer specific property requirements
<b>SURFACE FINISHES</b>	1BA & TR (Temper Rolled), 2B
<b>SURFACE ROUGHNESS</b>	4 — 12 RA or as required
<b>SURFACE CLEANING</b>	Cleaning as thin as .0008"
<b>FLATNESS AS ROLLED</b>	3% of thickness. Tension leveling for thin gauges is available upon request
<b>CAMBER</b>	As narrow as 1/2" wide: 1/4" maximum in any 8 foot length Less than 1/2" wide: 1/2" maximum in any 8 foot length
<b>COIL ID</b>	6", 8", 16"
<b>LOT SIZE</b>	50 lbs. minimum

*Please contact us for additional grades and sizes at [sales@upmet.com](mailto:sales@upmet.com)*

**QUALITY SOLUTIONS. TRUSTED PARTNERS.**