Contact



www.upmet.com



sales@upmet.com



888.282.3292



Aerospace Fastener Medical Power Generation Oil and Gas Semiconductor



Stainless Steel Nickel Allovs Cobalt Alloys Cobalt Chrome Moly Titanium Duplex Stainless Steel **PRODEC©** Aluminum Alloy Steel



AS9100D ISO 9001: 2015 ISO 13485 \$1000/ S-SPEC 1 Pratt & Whitney LCS **Certifications** Laser Cutting Approvals: •NADCAP AC7116 •GE \$422

FIRSTCUT+® Processing Services

Cut-To-Length Leveling Slitting Edging Shearing Laser Cutting

Laser Gauge Measurement Water Jet Cutting Sawing

Precision Cold Saw Cutting Precision Blanks First Stage Machining Heat Treating Ultra-Sonic Testing Boring Trepanning Deburring



Locations



Cincinnati, OH (headquarters) Oakland, CA Los Angeles, CA Hartford, CT Chicago, IL Greenville, SC Belfast, Northern Ireland Budapest, Hungary Singapore

Company Overview

United Performance Metals (UPM), an O'Neal Industries affiliate company, is a global distributor of high-performance speciality metals. UPM's full line of high strength, high temperature, and corrosion resistant materials coupled with FIRSTCUT+® Processing Services provides quality solutions which support a variety of industries.



To be recognized by our customers, employees and owners to be the best performing speciality metals service center.



To deliver quality products and services to our customers through world class processes, people and facilities.

Respect- We respect our customers, employees, suppliers, community and shareholders.

We exemplify this through a culture of honesty and integrity that stresses 'doing what is right' for all groups and individuals. Employee safety is held to the highest standard.

Values

Leadership- We train, coach, encourage and reward to create an empowered work force that is responsible for meeting the expectations of our customers, employees, suppliers and shareholders.

Continuous Improvement- We are committed to an environment of continuous improvement in everything we do. We do this by understanding customer, employee and supplier expectations and continuously working to innovate and improve products, services and processes.

Follow











| Stainless Steel | Sheet/ Coil Gauge Ranges | Bar Size Ranges | Plate Gauge Ranges |
|-----------------|-----------------------------|--|-----------------------|
| Custom 455 | | 0.1875"- 2.000" | |
| Custom 465® | | 0.3125"- 1.250" | |
| Greek Ascoloy | | 0.260"- 6.000" | |
| 15-5 PH | | 0.500"- 6.500" | |
| 17-4 PH | 0.029"- 0.130" | 0.250"- 5.000" | 0.1875"- 2.500" |
| 17-7 PH | 0.018"- 0.187" | | 0.1875" |
| 301 | 0.018"- 0.130" | | |
| 301-1/4 | 0.011"- 0.130" | | |
| 301-1/2 | 0.009"- 0.130" | | |
| 301 FH | 0.009"- 0.065" | | |
| 302 | 0.007"- 0.145" | | 0.1875"- 0.250" |
| 303 | | | 0.1875"- 4.000" |
| 304/304L | 0.018" - 0.130" | 2.000", 4.000", 7.250" | |
| 316/316L | 0.018"- 0.130" | 0.125"- 3.000" | |
| 316LS/316LVM | | 0.1875"- 0.4375" | |
| 317L/LM/LMN | | | 0.625"- 1.250" |
| 321 | 0.011"- 0.130" | Rnd. 0.375"- 9.000" Hex 0.4375"- 1.125" | 0.250" |
| 347 | 0.018"- 0.130" | 0.3125"- 8.000" | |
| 410 | 0.018"- 0.145" | 1.000"- 8.000" | 0.1875"- 1.000" |
| 416 | | | 0.1875"- 4.000" |
| 422 | | 0.500"- 13.000" | |
| 440C | | | 0.1875"- 2.500" |

| | Ouplex Stainless Steel | Sheet/ Coil Gauge Ranges | Bar Size Ranges | Plate G Ranges | _ |
|---|------------------------|-----------------------------|-----------------|-------------------|--------|
| 2 | 2205 | | | 0.125"- | 1.000" |

| PRODEC® | Sheet/ Coil Gauge Ranges | Bar Size Ranges | Plate Gauge Ranges |
|------------|-----------------------------|-----------------|-----------------------|
| 304P/304LP | | | 0.1875"- 3.500" |
| 316P/316LP | | | 0.1875"- 3.500" |

"We are committed to long-term success for the customers and markets we serve."

Tom Kennard, President of United Performance Metals

| Nickel Alloys | Sheet/ Coil Gauge Ranges | Bar Size Ranges | Plate Gauge Ranges |
|----------------|-----------------------------|---------------------|-----------------------|
| Alloy X | 0.020" - 0.130" | 0.250"- 6.500" | 0.1875" |
| Alloy 6230 | 0.025" - 0.125" | | |
| A286 | 0.016" - 0.125" | 0.250"- 6.000" | |
| A286CR/15%-17% | | 0.260" - 1.510" | |
| A286CR/40%-60% | | 0.385" - 1.260" | |
| C263 | 0.040"- 0.125" | | 0.1875"- 2.450" |
| K500 | | 0.500"- 1.750" | |
| R405 | | Hex. 0.687"- 2.750" | |
| Waspaloy CR® | | 0.260" - 0.4475" | |
| Waspaloy®5706 | | 0.375" - 2.000" | |
| Waspaloy®5708 | | 0.218" - 1.010" | |
| X750 | 0.023" - 0.075" | | |
| 600 | 0.018" - 0.065" | | |
| 625 | 0.016" - 0.130" | 0.375" - 7.000" | 0.1875" - 2.000" |
| 718 | 0.016" - 0.165" | 0.250" - 10.000" | 0.1875" - 2.000" |
| 718/B50809D | | 1.072" - 7.125" | |
| 718 CR | | 0.260" - 1.635" | |
| 901 | | 2.500" - 12.250" | |

| Cobalt Alloys | Sheet/ Coil Gauge Ranges | Bar Size Ranges | Plate Gauge Ranges |
|---------------|-----------------------------|-----------------|-----------------------|
| Alloy 159® | | 0.774" | |
| L605 | 0.029"-0.065" | 0.201"- 4.000" | |
| MP35N® | | 0.325"- 0.649" | |
| 188 | 0.020"- 0.083" | 0.375"- 4.000" | |

| Colbalt Chrome Moly | Sheet/ Coil Gauge Ranges | Bar Size Ranges | Plate Gauge Ranges |
|---------------------|-----------------------------|-----------------|-----------------------|
| CCM | | 0.250" - 2.000" | |

Product Forms











| Titanium | Sheet/ Coil Gauge Ranges | Bar Size Ranges | Plate Gauge Ranges |
|---------------|-----------------------------|-----------------|-----------------------|
| CP Grade 2 | 0.016"- 0.125" | 0.125"- 0.500" | 0.250"- 0.500" |
| CP Grade 3 | 0.012"- 0.063" | | |
| CP Grade 4 | 0.012"- 0.080" | 0.250" | 0.250" |
| Ti-6AL-4V | 0.012"- 0.125" | 0.2499"- 8.500" | 0.250"- 4.000" |
| Ti-6AL-4V ELI | | 0.125"- 3.000" | 0.250"- 1.000" |

| Aluminum | Sheet/ Coil Gauge Ranges | Bar Size Ranges | Plate Gauge Ranges |
|----------|-----------------------------|-----------------|-----------------------|
| Mic 6® | | | 0.2500"- 2.000" |
| 6061 | | | 0.1875"- 6.000" |

| Alloy Steels | Sheet/ Coil Gauge Ranges | Bar Size Ranges | Plate Gauge Ranges |
|----------------|-----------------------------|-----------------|-----------------------|
| B-16 | | 1.000"- 7.000" | |
| CrMoV | | 4.000"- 27.750" | |
| Nitralloy 135® | | 2.000"- 7.000" | |

U.S. and International Stocking Locations



